

Date issued: 18.12.2014 Version: 0001
Revision Date: 20.01.2016

N/A = Not Applicable
DNA = Data Not Available

Knauf Aquapanel GmbH & Co. KG

1. Identification of the substance / preparation and company

1.1 Substance / preparation

Commercial product names: AQUAPANEL® Cement Board Indoor, AQUAPANEL® Cement Board Indoor -

Lighter. Easier. Faster, AQUAPANEL® Cement Board Outdoor,

AQUAPANEL® Cement Board Floor Tile Underlay, AQUAPANEL® Cement

Board SkyLite, AQUAPANEL® Cement Board Universal Fiberglass reinforced carrier plates and façade backing boards

Product-code. Order-No. Composition-No.

Application

1.2 Manufactor

Knauf Aquapanel GmbH & CO. KG

Zur Helle 11 D- 58638 Iserlohn

Telephone: int+49-(0)2374-50360 Fax: int+49-(0)2374-5036300

e-mail: aquapanel.info@knauf.com

1.3 Emergency telephone

Giftnotruf Berlin, Beratungsstelle für Vergiftungserscheinungen und Embryonaltoxikologie

Telefon: int+49-(0)30-19240

2. Classification according to Regulation (EC) No 1272/2008 and Directive 67/548/EEC and 1999/45/EC

Not classified. Hazards are not expected.

2.1 Description of hazards

Hazards are not expected.

2.2 Impact on human health

Hazards are not expected.

2.3 Impact on environment

Water hazard class WGK 1 (self-classified)

3. Composition / Information on ingredients

The product is an article according to Regulation 1907/2006. The function of an article is mainly determined due to the specific shape, surface and less due to the chemical composition. The carrierplate is composed of cement, fillers and mineral fibres.

3.1 Hazardous constituents subjekt to the regulation 67/548/ECC and Regulation 1907/2006/EC

CAS-No.	EC-No.	Chemical name	m %	Symbol	R-Phrases
N/A	N/A	N/A	N/A	N/A	N/A

see for R-Phrases/H-Phrases at chapter 16.2.

3.2 Substances, not listed in chaptert 2.1

(see chapter 8.) Portlandcement CAS 65 997-15-1 / EC 266-043-4

3.3 additional information low chromate concentration according to TRGS 613. (Germany), 1907/2006/EC Annex XVII, No 47, Chemikalienverbots VO

4. First Aid Measures

4.1 General information Consult physician immediately, if discomfort occurs after contact with the product.

4.2 *Inhalation* Remove the person to fresh air, obtain medical assistance.

4.3 Skin contact Flush immediately with plenty of water and soap. Remove contaminated clothing

immediately from skin.

4.4 Eye contact Irrigate with plenty of water and obtain medicial advice.
4.5 Ingestion Do not induce vomiting. Consult physician immediately.

4.6 Information for the physician

Symptoms N/A

HazardsHazards not expectedTreatmentsymptomatic treatment

4.7 First aid equipment N/A4.8 Additional Information None

Commercial product name: AQUAPANEL® Cement board
Manufactor/supplier: Knauf Aquapanel GmbH & Co. KG
Zur Helle 11, D-58638 Iserlohn

Telephone: int+49-(0)2374-50360 Date issued: 19.08.2013
Product code: Revision Date: 20.01.2016

5. Fire-fighting Measures

5.1 Suitable extinguishing media

The product is not flammable.

5.2 Unsuitable extinguishing media

The product is not flammable.

5.3 Special hazards caused by substance or preparation itself, its combustion products or released gases

Hazards not expected.

5.4 Special protective equipment

Adapt equipment on surrounding combustion.

5.5 Additional information

None

6. Accidential release Measures

6.1 Personal protection (see chapter 8., personal protection)

Ventilate sufficiently.

6.2 Environmental protection (see chapter 13., disposal)

Keep away from surface water, ground water and drains.

6.3 Methods on cleaning up

Absorb mechanically and dispose of according to legal provisions.

6.4 Additional information

None

7. Handling and Storage (National regulations see chapter 15.,16.)

7.1 Handling

Advice on safe handling

See chapter 8

Fire control and explosion prevention

No special measures

Additional requirements

None

7.2 Storage

Requirements for storage an vessels

None

Advice on storage compatibility

Keep away from acids

Further information on storage conditions

Keep dry

Storage category

13 (VCI storage concept)

7.3 Special usage

DNA

8. Exposure and personal protection

8.1 exposure limit values

CAS-No.	Chemical Name	Limits	Type of Limit
N/A	portlandcement (dust)	5 mg/m³	total inhalable
N/A	general threshold limit value(dust)	$1,25 \text{ mg/m}^3$	total respirable
N/A	general threshold limit value(dust)	10 mg/m ³	total inhalable

8.2 Limitation and control of occupational exposure

See chapter 7

Personal protection

Respiratory protectionNot applicable in duly practice. In case of dust formation use dust

mask P2 or dust exhausting equipment.

Hand protection Use protective gloves.

Eye protection Protective goggles where eye contact is possible.

Body protection Wear protective overalls and footwear.

Skin protection Use revitalising cream

General measures Wash hands before breaks and end of work. When using do not drink

or eat.

Commercial product name: AQUAPANEL® Cement board Manufactor/supplier: Knauf Aquapanel GmbH & Co. KG Zur Helle 11, D-58638 Iserlohn

Telephone: int+49-(0)2374-50360 Date issued: 19.08.2013 Product code: Revision Date: 20.01.2016

9. Physical and chemical properties

9.1 General information

Colour: cementgrey Form: solid **Odour:** Odourless

9.2 Important information on health- and environmental safety

> Melting point: >1000 °C Grammage (kg/m²): 17

Density (g/cm³): 1200 up to 1450

9.3 Additional information None

10. Stability and reactivity

10.1 Hazardous reactions

No hazardous reactions known.

10.2 Hazardous decomposition products

No hazardous decomposition products known.

10.3 Additional information

None

11. **Toxicological information**

11.1 Toxicological tests

11.1.1 Acute toxicity / specific result of animal experiments

DNA LD50 rats, oral (mg/kg) LC50 rats, inhalation (mg/l/4h)DNA LD50 rats, dermal (mg/kg) > 2000

11.1.2 Irritancy and corrosivensess / sensitising effect

Skin irritation DNA

Eye irritation Direct contact on mucous membranes may cause irritation of the eyes. Mechanic irritation possible (wear safety glasses). Skin sensitation

Repeated or prolonged contact may cause skin irritation (wear

impervious gloves).

11.1.3 Subchronic, prolonged toxicity / carcinigenity, mutagenicity and reproductive toxicity

Eeffects

Carcinogenity DNA Mutagenicity DNA Reproductive toxicity DNA Chronic Toxicity DNA

11.1.4 Additional Information

11.2 Past exeirience

11.2.1 Relevant oberservations for classification Due to the hydrophobic properties and the alkalinity of cement

direct contact on mucous membranes may cause irritation of

the eyes.

11.2.2 Other oberservations Repeated or prolonged contact may cause skin irritation. 11.3 General information Toxicity studies have not been conducted on this product.

Commercial product name: AQUAPANEL® Cement board
Manufactor/supplier: Knauf Aquapanel GmbH & Co. KG
Zur Helle 11, D-58638 Iserlohn

Telephone: int+49-(0)2374-50360 Date issued: 19.08.2013
Product code: Revision Date: 20.01.2016

12. Ecological information

12.1 Ecotoxicity

Aquatic Toxicity:

 96 h LC50
 (fish)
 DNA

 48 h EC50
 (Daphnia)
 DNA

 72 h IC50
 (Alga)
 DNA

 Waste water treatment plant:
 DNA

12.2 Mobilityt

DNA

12.3 Persistance and degradabillity

DNA

12.4 Bioaccumulative potential

DNA

12.5 Other adverse effects

Ozon depletion DNA.
Potential for photochemical ozone formation DNA
AOX DNA

12.6 Additional information

COD-Value DNA
BOD-Value DNA

Substances according to regulations 2006/11/EC

None

12.7 Water endangerment category

Slightly water endangering (WGK1), self-classified Keep away from drains, surface water amd groundwater

12.8 Result of PBT assessment

DNA

13. Advice on disposal

13.1 Disposal according to national regulations (Abfallverzeichnis Verordnung)

Notice:

Category: Construction and demolition wastes

Description: other construction and demolition wastes

Waste code : 17 09 04 mixed construction and demolition wastes other than those mentioned

in 17 09 01, 17 09 02 and 17 09 03

Disposal : D 1 above/ in ground waste storage (e.g. landfill)

Recycling: R 3/5 utilisation/recuperation of organic materials, those that are not used as

solvents

Ultilisation/recuperation of other organic materials

13.2 uncleaned package

Advice: containers are to be emptied. The containers can be reused. Recommended cleaning procedure: a removal of the dry remaining contents is possible.

14. Transport information

14.1 Land transport ADR / RID / GGVSE
 14.2 Marine transport IMDG / GGVSee
 14.3 Air transport ICAO / IATA
 Not classified as hazardous for transport.
 Not classified as hazardous for transport.

Commercial product name: AQUAPANEL® Cement board
Manufactor/supplier: Knauf Aquapanel GmbH & Co. KG
Zur Helle 11, D-58638 Iserlohn

Telephone: int+49-(0)2374-50360 Date issued: 19.08.2013
Product code: Revision Date: 20.01.2016

15. Regulatory information

15.1 National regulations

Advice on: N/A
Statutory order on hazardous incidents: N/A
Classification acc. to VbF: N/A
Technische Anleitung Luft: N/A

Water hazard class: WGK 1 (self-classified)

Other regulations, restrictions:

None known

15.3 Chemical Safety Report

DNA

16. Additional information

16.1 Record retention NA

Customers industry, private consumers

16.2 Wording ofP- and S-phrases

P280 – Wear protective gloves/protective clothing/eye protection/face protection.

P305/P351/P338/P310—IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

P302/P352/P333/313 – IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.

P261/P304/P340/312 – Avoid breathing dust. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

S24: Avoid contact with the skin

S25: Avoid contact with eyes

S28: After contact with skin wash with plenty of water

S36: Wear suitable protective clothing

S37: Wear suitable gloves

16.3 responsible division / contact / telephone

Contact information:

KNAUF Aquapanel GmbH & Co. KG, Zur Helle 11, D-58638 Iserlohn

Telephone: int+49-(0)2374-50360 Fax: int+49-(0)2374-5036300

Version: 0001

changes in documentation:

16.4 This data sheet provides you with reference points for the safe handling, storage, transport and disposal. The information is based on the current level of knowledge and assure no certain characteristics. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with handling, storage, use or disposal of the products AQUAPANEL® Cement board.